

Syndiotactic Polystyrene

92S11

October 1994

TABLE OF CONTENTS

	Page
I SUMMARY	1
II INTRODUCTION	8
III PHYSICAL PROPERTIES	10
IV CHEMISTRY	22
V TECHNOLOGY	28
A. PROCESS DESIGN	28
B. ECONOMICS	34
VI MARKET ANALYSIS	38
A. ELECTRICAL/ELECTRONICS	38
B. AUTOMOTIVE	40
C. FOOD PACKAGING	42
D. INDUSTRIAL FILMS	45
E. OTHER MARKETS	47
1. Specialty Monofilament Fibers	47
2. Fluoropolymers	48
3. Performance Thermoplastics	48
REFERENCES	50

TABLES

		Page
Table I.1	Properties of Polystyrenes and Crystalline Engineering Thermoplastics	3
Table III.1	Properties of Polystyrenes and Crystalline Engineering Thermoplastics	12
Table III.2	Chemical Resistance of SPS	12
Table III.3	Properties of SPS and Selected Glass Filled Engineering Thermoplastics	13
Table III.4	Properties of Biaxially Oriented Films, 25 μ M	21
Table V.A.1	SPS Polymerization Catalyst Parameters	28
Table V.B.1	Cost Estimate of SPS Production via the Bulk Process	35
Table V.B.2	Catalyst Costs	36
Table VI.A.1	Triregional Polyamide and Polyester Demand in Electrical/ Electronics Applications	40
Table VI.B.1	Triregional Demand for Polyamide and Polyester Used in Automotive Applications	42
Table VI.C.1	Triregional CPET Demand	44
Table VI.D.1	Triregional OPET Film Demand in Selected Applications, 1993	46

FIGURES

		Page
Figure III.1	Polystyrene Structures	10
Figure III.2	Properties of Composite Materials	14
Figure III.3	Dielectric Constant vs. Frequency in Composite Materials	16
Figure III.4	Density Comparison of Composite Materials	17
Figure III.5	Dimensional Stability of Composite Materials	18
Figure III.6	SPS Film Properties: Light Transmission vs. Wavelength	19
Figure III.7	SPS Film Properties: Dielectric Constant vs. Frequency	20
Figure IV.1	Phenyl-Phenyl Interaction and Chain Propagation	27
Figure V.A.1	SPS Polymerization Process	30
Figure V.A.2	SPS Polymer Recovery	31
Figure V.A.3	SPS Process - Typical Finishing Area (dry end)	33
Figure V.B.1	Effect of Catalyst System Cost on SPS Production Costs	37